

# NYSTEIN GAP PAD Flextein® S51G

## Technical Data Sheet


### Product Description:

Flextein S51G is a 5.1 W/m·K and ultra soft thermal interface gap filler with great thermal performance and high compliance. The material yields extremely soft characteristics while maintaining elasticity and conformability. The Inherent natural tack on both sides assists in application and allows the product to effectively fill air gaps, enhancing the overall thermal performance. It is ideal for use to fill gaps between high-power, heat-generating components and related heat sinks, boards or chassis.

Flextein S51G is naturally tacky on both sides and requires only a light pressure during assembly to secure components without adhesive. The thickness of the product can be customized in the range of 0.5-10.0mm according to the needs of customers, and one-sided adhesive can also be selected for ease of use.

### Features & Benefits:

- Thermal conductivity 5.1 W/m·K
- Super soft, high compression
- Good compression resilience
- V-0 Flame retardant grade
- Thickness range 0.02" (0.50mm) to 0.40" (10.0mm)



### Typical Property Data:

Property	Unit	Parameter	Test Method
Appearance	--	Light Yellow	Visual
Thickness	mm	0.5 to 10.0	ASTM D374
Thermal Conductivity	W/m · K	5.1	ISO 22007-2
Hardness	Shore OO	35	ASTM D2240
Density	g/cm <sup>3</sup>	3.1	ASTM D792
Dielectric Strength	kV/mm	≥6.0	ASTM D149
Volume Resistivity	Ω · cm	≥ 1.0 × 10 <sup>12</sup>	ASTM D257
Dielectric Constant	1MHz	7.4	ASTM D150
Oil seepage rate	%	< 1	125°C&48h
Service Temp	°C	-40 to 150	Nystein
Flame Rating	—	V-0	94 UL
RoHS	—	Yes	Nystein

### Typical Application:


- Computers and servers and their peripherals
- Smartphone, Tablet Multimedia
- High-end network equipment
- Optical Communication Modules
- Military Products

### Configuration Available:

- Standard size 470×470 mm, sheet form and die-cut parts could be required.
- Standard thickness: 0.5mm (0.02") to 10.0 mm (0.40") in 0.5mm (0.02") increments. Can be customized according to customer needs
- Natural tack on one or both side option

### Ordering Guide:

Flextein® S51G-020 47004700 IR D1



**None:** Double side tacky **D1:** Single side tacky **A1:** Single side adhesive

**R:** Rectangular; **IR:** Irregular

**Size:** 470mm\*470mm

**Thickness:** 2.0mm

**Series:** S51G

### Storage conditions:

- Sealed at room temperature away from light, and stored in a dry place.
- Best Storage conditions: Temperature: 25°C (±3), Humidity: 50% (±10), can be stored for 12months.
- The materials taken out after opening may be contaminated during use, so please do not mix contaminated products with unopened products. Nystein assumes no responsibility for contaminated products or conditions other than the required storage conditions.
- For additional information, please contact your appropriate sales, technical support, or customer service representative promptly.

#### Declare

The information provided in this Technical Data Sheet (TDS), including product use and application recommendations, is based on our knowledge and experience with Nystein China products. The data contained in this TDS is for informational purposes only and is believed to be reliable. To obtain official product specifications for a specific product end use, please contact the sales, Application Engineer or customer service person with whom you are in contact.

We are not responsible for results obtained by others using methods beyond our control. This product may have a variety of applications and different operating conditions in your environment that are beyond our control. Therefore, Nystein China assumes no responsibility for the suitability of our products for the processes and conditions under which you will use them and for the intended applications and results. We strongly recommend that you conduct tests to confirm the suitability of our products prior to their use.

This product is protected by one or more of Nystein China Chinese patents or patent applications.